



## PRODUCT DATA

### Castrol Dual Range HV

Castrol Dual Range HV Hydraulic Fluids are exceptional multi-viscosity hydraulic fluids that provide proven anti-wear protection coupled with very shear stable polymers and anti-foam additives for a balanced package. An extreme load carrying capability is indicated where Castrol Dual Range HV Hydraulic Fluids pass the FZG Load carrying test at Stage 12. This outstanding performance provides the extra measure of protection required in high load applications such as hydrostatic transmissions and high speed/high pressure hydraulic circuits.

Castrol Dual Range HV Hydraulic Fluids' high viscosity indexes and their low pour points ensure extra pump protection and efficiency in cold weather starts and provide needed viscosity protection at higher operating temperatures. The products are dyed purple to facilitate leak detection.

### Features and Benefits:

- Very shear stable polymers provide universal applications under a wide range of ambient conditions
  - Excellent viscosity at operating temperatures (particularly under extreme conditions)
- Less wear promotes longer equipment life and better productivity through maximum hydraulic system efficiency
- Excellent vane and piston pump performance that meets major hydraulic pump manufacturers' requirements
  - Less failure of hydraulic circuits
  - Less equipment repair for long term trouble-free service
- Outstanding hydrolytic stability provides additional protection against corrosion in the presence of water. Systems operate more efficiently, while reducing maintenance costs.
- Exceptional oxidation and thermal stability provides resistant to thermal degradation in the presence of entrained air and catalyzing metals
- Prevents the formation of sludge and varnish deposits during periods of extended high temperature operation
- Resistant to the formation of oxidation acids allowing longer pump life, less wear, less down time

### Warranty and Protection Requirements:

- Exceeds all manufacturer's warranty requirements for applications requiring a Dennison HF-O approved hydraulic fluid

### Industry and OEM Specifications and Approvals:

- Denison HF-O, HF-1, HF-2 approved
- Vickers 35VQ25A - meets performance requirements
- Vickers M-2950-S Mobile Hydraulic Systems and I-286-S Industrial Hydraulic Systems
- Cincinnati Machine P-68 (ISO 32), P-70 (ISO 46) and P-69 (ISO 68) approved
- Meets Racine S106
- Meets Joy Mining Machinery HO-T (AW 46), HO-S (AW 68)
- Meets DIN 51524 requirements



**Typical Properties:\***

ISO Grade	Units	Method	Typical Results			
			22	46	68	100
Viscosity	40°C, cSt	ASTM D-445	22.1	46.5	68	100.3
	100°C, cSt	ASTM D-445	4.8	7.9	10.6	13.9
	100°F, SUS	ASTM D-2161	107	216	314	459
	210°F, SUS	ASTM D-2161	42	52	61.4	73.6
Viscosity Index		ASTM D-2270	143	143	146	141
Flash Point	°C (°F)	ASTM D-92	176(349)	232(450)	240(464)	251(484)
Pour Point	°C (°F)	ASTM D-97	-54(-65)	-45(-49)	-39(-38)	-36(-33)
Dielectric Breakdown	Voltage, KV/0.1 inch	ASTM D-877	35	35	-	-
Gravity, API		ASTM D-287	36	34	30	29
Specific Gravity @60F	g/ml	ASTM D-1298	0.848	0.859	0.874	0.88
Pounds per Gallon		ASTM D-287	7.03	7.12	7.3	7.34

\* Due to continual product research and development, the information contained herein is based on products purchased in the U.S subject to change without notification. Typical properties may vary slightly.

**Part Numbers and UPCs:**

Grade	32	46	68	100
5 Gal. Pail Part No.	41557	42057	42257	
55 Gal. Drum Part No.	41559	42059	42259	42269
260 Gal. Tote Part No.	415547	420547	422547	
Bulk	41550	42050	42250	



### **Health and Safety:**

Based on available information, this product is not expected to produce adverse effects on health when used for the applications referred to above and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contact office, or via the Internet at [www.castrol.com/us](http://www.castrol.com/us). This product should not be used for purposes other than the applications referred to above. If disposing of used product, take care to protect the environment, return used oil to collection center.

BP Lubricants USA Inc.  
1500 Valley Road  
Wayne, NJ 07470  
Telephone: 1.800.462.0835  
[contactus@bp.com](mailto:contactus@bp.com)  
©2010 BP Lubricants USA Inc. All rights reserved.

[www.castrol.com/us](http://www.castrol.com/us)