

Product Data



Castrol Fifth Wheel Grease

Castrol Fifth Wheel Grease has been designed specifically for fifth wheel applications where stay-in-place performance is critical under all weather and application conditions. Fifth wheels typically experience extreme fretting, which is defined as the removal of finely divided metal particles from rubbing surfaces due to oscillation, sliding, or vibration. **Castrol Fifth Wheel Grease** rises to the challenge in multiple fifth wheel applications with maximum stay-in-place performance. Its graphite/moly formulation and high percent of tackifiers give it a true affinity for metal surfaces. The tacky tenacious properties of the **Castrol Fifth Wheel Grease** coupled with 10% lubricating solids further enables this grease to provide outstanding adhesion to fifth wheels in even the toughest operating conditions.

Typical Analysis

Part Number	5552
NLGI Grade	2
Penetration (D-217) W60	270/268
Appearance	Black/Very Tacky
Water Sprayoff (D4049)%	Less than 10%
Copper Corrosion (D4048)	1b
Rust Prevention (D1743)	Pass
Lubricating solids (% wt.)	10
Pumpability – g/min (USS) @ 60°F	100

BP Lubricants USA Inc.
1500 Valley Road
Wayne, New Jersey 07470
Telephone 1.800.255.4417

Form 5552 3/22/2007

IT'S MORE THAN JUST OIL. IT'S LIQUID ENGINEERING.™

