

CASTROL Act>Evo X-Tra Offroad 4T Motor Oil

Castrol Act>Evo X-Tra Offroad 4T Motor Oil with Trizone Technology is a premium quality part-synthetic 4-stroke engine oil. Its specially formulated Heat Protection Molecules work to protect your bike's engine against the build up of harmful high temperature deposits even when you work your bike hard. Evaluated in highly stressed, high temperature motocross and ATV engines, Castrol Act>Evo X-Tra Offroad provides exceptional engine deposit control, keeping pistons and oil ways clean during the hardships of extreme off road riding.

- Part-synthetic 4-stroke motorcycle and ATV engine oil
- Specifically formulated for ATVs and offroad dirt bikes
- Excellent oil consumption control
- Suitable for all makes of 4-stroke Japanese and North American ATV and dirt bike engines running on leaded or unleaded gasoline
- For more information please visit www.castrol.com/motorcycle.

TYPICAL PROPERTIES*

Test	Method	Typical Results	
		10W-40	20W-50
API Service		SG	SG
JASO Service		MA2	MA2
Specific Gravity, 60° F	ASTM D1298	0.875	0.885
Pounds per Gallon		7.3	7.3
Viscosity, cSt 100°C	ASTM D445	14.0	19.4
Low Temperature (°C) Cranking Viscosity, cP max	ASTM D5293	7,000 @ -25	9,500 @ -15
Low Temperature (°C) Pumping Viscosity, cP max	ASTM D4684	60,000 @ -30	60,000 @ -20
High Temperature High Shear Rate Viscosity, cP min @ 150°C	ASTM D4683	2.9	3.7
Calcium % wt.	ASTM D4951	0.061	0.061
Zinc % wt.	ASTM D4951	0.113	0.103
Phosphorus % wt.	ASTM D4951	0.103	0.101

Note: This information is based on products sold in the U.S. Due to continual product research and development, the information is subject to change without notification. Typical properties may vary slightly.

More technical information is available by contacting Castrol directly at 1-800-462-0835.

PART NUMBER & UPC INFORMATION

Packaged Goods

Case Size

10W-40	20W-50
12/1 Lt Plastic	12/1 Lt Plastic
12893	12894
00593-4	00592-7
00593-4	00592-7

Case Part No.

Bottle / Unit UPC

Case UPC

Health & Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the applications referred to above and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contact office, or via the Internet. This product should not be used for purposes other than the applications referred to above. If disposing of used product, take care to protect the environment, return used oil to collection center.

© 2007 BP Lubricants USA Inc. All rights reserved.

BP Lubricants USA Inc.
1500 Valley Road
Wayne, NJ 07470

Telephone: 1-800-462-0835
E-mail: contactus@bp.com
Website: www.castrol.com/atf

IT'S MORE THAN JUST OIL. IT'S LIQUID ENGINEERING.™

