

## CASTROL Domestic Multi-Vehicle Automatic Transmission Fluid (ATF)

Castrol Domestic Multi-Vehicle Automatic Transmission Fluid is for use in older Ford & General Motors vehicles.

- Enhanced friction durability for smooth transmission performance.
- Meets DEXRON®-III H requirements. Also satisfies requirements of DEXRON®, DEXRON®-III, IIE, and II. Do not use this ATF in applications calling for DEXRON®-VI.
- Meets MERCON® requirements. May also be used in power steering applications where MERCON® is required. Use Castrol Type F ATF in applications calling for Type F. Do not use this ATF in applications calling for MERCON® V or MERCON® SP.
- For more information please visit [www.castrol.com/atf](http://www.castrol.com/atf).

### TYPICAL PROPERTIES\*

Test	Method	Typical Results
Viscosity@ 40°C, cSt	ASTM D-445	38.1
Viscosity@ 100°C, cSt	ASTM D-445	7.9
Viscosity Index	ASTM D-2270	186
Color, Typical	ASTM D-1500	7.0
Appearance		Red
Brookfield Viscosity @ -40 C, max, cP	ASTM D-2983	17,000
Pour Point, °F (°C)		-45 (-43)
Flash Point, COC, min °F (°C)	ASTM D-92	350 (177)
Specific Gravity, 60°F	ASTM D-1298	0.863
Pounds per Gallon		7.19

Note: This information is based on products sold in the U.S. Due to continual product research and development, the information is subject to change without notification. Typical properties may vary slightly.

More technical information is available by contacting Castrol directly at 1-800-462-0835.

### PART NUMBER & UPC INFORMATION

#### Packaged Goods

Case Size	12/1 Qt	3 x 1 Gallon
Case Part No.	12061	03520
Bottle / Unit UPC	0-79191-00462-3	0-79191-33520-8
Case UPC	0-79191-12462-8	0-79191-03520-7

#### Pail / Drum / Bulk

Unit Size	16 Gal Pail	55 Gal Drum	Bulk
Part No.	0463	0464	0460

#### Health & Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the applications referred to above and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contact office, or via the Internet. This product should not be used for purposes other than the applications referred to above. If disposing of used product, take care to protect the environment, return used oil to collection center.

© 2007 BP Lubricants USA Inc. All rights reserved.

**BP Lubricants USA Inc.**  
1500 Valley Road  
Wayne, NJ 07470

Telephone: 1-800-462-0835  
E-mail: [contactus@bp.com](mailto:contactus@bp.com)  
Website: [www.castrol.com/atf](http://www.castrol.com/atf)