

CASTROL GT Power Steering Fluid

Castrol GT Power Steering Fluid is recommended for complete fluid replacement and "top-up" in most cars and light trucks.

- Helps prevent leaks, squeals, rust and corrosion.
- Protects seals and hoses.
- Smooths power steering operation.
- Resists foaming tendency.
- Provides excellent protection against fluid oxidation.

Warranty and Protection Requirements

- Exceeds performance requirements of GM9985010 (Part No. 1050017 and 1052884), Chrysler MS-5931 (Hydro boost systems), Saab (Part No. 45-30 09-800) and Volkswagen TL-VW-570-26 (Part No. ZVW 239-902). Suitable for use in applications where DEXRON, DEXRON-II, DEXRON-IID, DEXRON-III or MERCON is required.
- For more information please refer to your owner's manual or visit www.castrol.com.

TYPICAL PROPERTIES*

Test	Method	Typical Results
Viscosity@ 40°C, cSt	ASTM D-445	32
Viscosity@ 100°C, cSt	ASTM D-445	7.5
Viscosity Index	ASTM D-2270	214
Color, Typical	ASTM D-1500	7.0
Appearance		Clear, straw-colored
Brookfield Viscosity @ -40 C, max, cP	ASTM D-2983	20,000
Flash Point, COC, min °F (°C)	ASTM D-92	350 (177)
Specific Gravity, 60°F	ASTM D-1298	0.85
Pounds per Gallon		7.14

Note: This information is based on products sold in the U.S. Due to continual product research and development, the information is subject to change without notification. Typical properties may vary slightly.

More technical information is available by contacting Castrol directly at 1-800-462-0835.

PART NUMBER & UPC INFORMATION

Packaged Goods

Case Size	12/ 12 oz bottles
Case Part No.	12492
Bottle / Unit UPC	0-79191-00492-0
Case UPC	0-79191-12492-5

Health & Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the applications referred to above and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contact office, or via the Internet. This product should not be used for purposes other than the applications referred to above. If disposing of used product, take care to protect the environment, return used oil to collection center.

© 2007 BP Lubricants USA Inc. All rights reserved.

BP Lubricants USA Inc.
1500 Valley Road
Wayne, NJ 07470

Telephone: 1-800-462-0835
E-mail: contactus@bp.com
Website: www.castrol.com