

CASTROL SYNTEC Gear Oil 75W-90

Castrol SYNTEC Full Synthetic Gear Oil 75W-90 provides maximum protection under severe service conditions.

Key Benefits

- Added assurance during extended drain intervals.
- Improved thermal stability and excellent shear stability for superior wear protection.
- Full compatibility with all conventional and synthetic API GL-5 and MT-1 gear oils.

Warranty and Protection Requirements

- Exceeds the service fill requirements of conventional and limited slip differentials calling for SAE 75W-90 and API Service GL-5 specification.
 - Exceeds API Service GL-5 lubricant for extreme pressure conditions.
 - Exceeds API MT-1 lubricant for non-synchronized manual transmissions used in buses and heavy-duty trucks
 - Meets the requirements of Mack GO-H/S
- For more information please refer to your owner's manual or visit www.castrol.com.

TYPICAL PROPERTIES*

| Test | Method | Typical Results |
|---|-------------|-----------------|
| Grade | | 75W-90 |
| API Service | | GL-5, MT-1 |
| Mack Service | | GO-H/S |
| Viscosity, cSt 100°C | ASTM D-445 | 15.0 |
| Low Temp.(°C) Brookfield Vis. cst., max | ASTM D-2983 | 150,000 (-40) |
| Pour Point, °C max | ASTM D-97 | -39 |
| Flash Point, COC, °F(°C) min | ASTM D-92 | 390 (198) |
| Specific Gravity, 60°F | ASTM D-1298 | 0.86 |
| Pounds per Gallon | | 7.16 |

Note: This information is based on products sold in the U.S. Due to continual product research and development, the information is subject to change without notification. Typical properties may vary slightly.

More technical information is available by contacting Castrol directly at 1-800-462-0835.

PART NUMBER & UPC INFORMATION

Packaged Goods

| | |
|-------------------|--------------------|
| Case Size | 6/1 qt w/tip spout |
| Case Part No. | 06672 |
| Bottle / Unit UPC | 0-79191-00672-6 |
| Case UPC | 0-79191-06672-0 |

Pail / Drum / Bulk

| | |
|-----------|-------------|
| Unit Size | 120 lb drum |
| Part No. | 0472 |

Health & Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the applications referred to above and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contact office, or via the Internet. This product should not be used for purposes other than the applications referred to above. If disposing of used product, take care to protect the environment, return used oil to collection center.

© 2007 BP Lubricants USA Inc. All rights reserved.

BP Lubricants USA Inc.
1500 Valley Road
Wayne, NJ 07470

Telephone: 1-800-462-0835
E-mail: contactus@bp.com
Website: www.castrol.com