

PRODUCT DATA

Tection HD 10W-30

Protection for US technology trucks & equipment

Applications

Castrol Tection HD is a 10W-30 heavy duty diesel engine oil designed to provide superior performance and protection for US'02 technology EGR engines.

Its primary application is for US trucks, buses and equipment, including both EGR and non-EGR engines.

Features / Benefits

Castrol Tection HD 10W-30's special low ash formulation has been developed to provide excellent performance and protection for diesel engines.

User benefits include:

Superior soot handling capability. EGR engines can produce higher levels of soot in the oil, which could lead to blocked filters and resulting engine damage. Castrol Tection HD 10W-30's excellent dispersancy ensures that the soot is evenly dispersed to prevent engine harm. Maximum engine protection. Castrol Tection HD 10W-30's formulation ensures complete engine protection: the low ash additives minimize deposits, and the special viscosity controlling technology ensures the oil continues to protect against wear throughout the oil drain interval, even under severe operating conditions.

Specifications / Performance

- SAE 10W-30
 - API CI-4, CH-4, CG-4, SL
 - Cummins CES , 20076
 - Mack EO-M Plus
-

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Form No. 1852 Rev. 02/08/2008
(over)

BP Lubricants USA Inc.
1500 Valley Road
Wayne, New Jersey 07470

Telephone 1.800.255.4417

IT'S MORE THAN JUST OIL. IT'S LIQUID ENGINEERING.™



Tection HD 10W-30Protection for US technology trucks & equipment

Health, Safety and Environment

Health, safety and environmental information is provided for this product in the Materials Safety Data Sheet. This gives details of potential hazards, precautions and First Aid measures, together with environmental effects and disposal of used products.

Castrol International will not accept liability if the product is used other than in the manner or with the precautions or for the purpose/s specified. Before the product is used other than as directed, advice should be obtained from the local Castrol office.

Typical Characteristics

SAE 10W-30

<i>Test</i>	<i>Method(s)</i>	<i>Unit</i>	<i>Typical</i>
Density @ 15C, Relative	ASTM D1298	g/ml	0.89
Viscosity, Kinematic 100C	ASTM D445	mm ² /s	11.3
Viscosity, CCS -25C (10W)	ASTM D5293	cP	6613
Viscosity, Kinematic 40C	ASTM D445	mm ² /s	77
Noack Volatility	CEC L-40-A-93	% Loss	12
Ash, Sulphated	ASTM D874	% wt	1.2
Total Base Number, TBN	ASTM D2896	mg KOH/g	10.7
Pour Point	ASTM D97	°C	-45

The above figures are typical of those obtained with normal production tolerance and do not constitute a specification.

This Data Sheet and information it contains is considered to be accurate at the date of printing. No warranty or representation, expressed or implied, is made as to the accuracy or completeness of the data and information contained in this publication.

It is the User's obligation to evaluate and use products safely and within the scope advised in the data sheet and to comply with all applicable laws and regulations. No statement made in this publication shall be construed as a permission, recommendation or authorization given or implied to practice any patented invention without a valid license.

The Seller shall not be responsible for any loss or damage resulting from any hazards or risks identified in the data sheet and which are associated with petroleum products concerned (provided that this disclaimer shall not affect any statutory rights of the Buyer of the petroleum products concerned).