

# Super Snowmobile 4T® Full Synthetic

SUPER PROTECTION

## Description

Castrol Super Snowmobile 4T® Full Synthetic is suitable for Severe Cold Weather Applications.

- Ambient operating temperatures range -40°C to +25°C
- Meets or exceeds API-SN
- Not suitable for wet clutch applications

## Typical Characteristics

| Name                            | Method     | Units              | Typical     |
|---------------------------------|------------|--------------------|-------------|
| Density @ 15°C                  | ASTM D4052 | g/ml               | 0.845       |
| Appearance                      | Visual     |                    | Clear Amber |
| Viscosity, Kinematic 100°C      | ASTM D445  | mm <sup>2</sup> /s | 9.0         |
| Viscosity, Kinematic 40°C       | ASTM D445  | mm <sup>2</sup> /s | 48.0        |
| Viscosity Index                 | ASTM D2270 |                    | 171         |
| Cold Cranking Viscosity @ -35°C | ASTM D5293 | mPa.s              | 5800        |
| Pour Point                      | ASTM D5949 | deg C              | -48         |

## Suitable for use in the following applications:

• API SN

## Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

## Product Details

| Product   | Part Number | Pack Size | UPC Bottle   | UPC Case     |
|---|-------------|-----------|--------------|--------------|
| Castrol 4T Stroke Snowmobile Full Synthetic Oil, 6X1L | 0017538     | 1L        | 056012024206 | 056012025166 |

Super Snowmobile 4T® Full Synthetic  
20 June 2024

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Wakefield Canada, Limited, 3620 Lakeshore Blvd West, Toronto, Ontario, Canada - M8W 1P2  
Phone 1-800-268-5339 Fax 416-252-7315 • Trade: 1 888 CASTROL  
Consumer: 1 800 CASTROL • Technical Inquiries: 1 800 462-0835  
www.castrol.com info@wakefieldcanada.ca  
WAKE3420 - v1