



Castrol Trans C 30

TO-4 Transmission Fluid

Description

Castrol Trans C, Transmission Drive Train Oil, meets the stringent Caterpillar TO-4 Fluid requirements, particularly where paper and elastomer disc materials are utilized and friction retention must be optimized for extended clutch life and slippage control under severe high load operations. While commercial engine oil technology excelled in the previous Caterpillar required CD/TO-2 specification where the bronze clutches prevailed, Castrol Trans C provides field-tested technology to ensure durability under today's strenuous operating conditions and where significant clutch material changes have taken place.

Castrol Trans C will also provide Detroit Diesel Allison C-4 performance. **CASTROL TRANS C** excels in many on and off-highway hydraulic oil applications.

Castrol Heavy Duty's traditional quality approach prevails in our "Trans C Fluid" by having premium base oil selection (high viscosity indexes) coupled with select additives for noted oxidation stability, rust and corrosion protection, foaming inhibition, anti-wear protection, mild "EP" and assured excellent pumpability in the "SAE 10W" or ISO 32 grade.

Advantages

- Designed specifically for transmission, wet disc brakes and final drives.
- Substantially improved friction and anti-wear performance compared to CD/TO-2 fluids.
- Longer equipment life and reduced risk of field failure.
- Formulated to provide controlled friction performance with several different friction modifiers (both metallic and non-metallic).
- Eliminate field failure problems experienced with CD/TO-2 fluids such as excessive brake noise, weakening of the binder in paper materials and embrittlement of elastomeric materials for trouble free equipment life.
- Stable frictional performance over vehicle life.
- No degradation of frictional performance or clutch slippage, even under high loads on an incline.
- Excellent oxidative stability control as shown by performance in Allison C- 4/Dexron II Oxidation Test (THOT).
- Sludge control prevents deposits from blocking lubricating passages.
- Excellent final drive protection for gears. Margin of safety for severe service.
- Excellent protection in hydraulic systems to include high pressure systems.
- Versatility of fluid for consolidation in on and off-highway equipment.
- Protection against copper corrosion and rust.
- Equipment parts run "clean" for trouble free operation.
- Maximum foam protection.
- Ensures no fluid loss to foaming, even with water contamination.
- Protection against fluid overflow and fire hazards for worker safety.
- Excellent low temperature fluidity
- Easier starts with less wear at cold temperatures for longer transmission life and increased worker productivity.

Warranty and Protection Requirements:

- Exceeds all manufacturer's warranty requirements for applications requiring a transmission fluid meeting the Caterpillar TO-4 specification.

OEM Specifications:

- Meets or exceeds Caterpillar TO-4 requirements
- Vickers 35VQ25 Vane Pump Performance

Typical Physical Characteristics

Test	Method	Typical Results
SAE Grade		30
Viscosity, 40° C, cSt	ASTM D-445	97
Viscosity, 100° C, cSt	ASTM D-445	11
Viscosity Index	ASTM D-2270	99
Flash Point, °C (°F)	ASTM D-92	220(428)
Pour Point, °C (°F)	ASTM D-97	-39(-38)
FZG Gear Scuffing	ASTM D-5182	11 Pass
Gravity, API	ASTM D-287	27.9
Pounds per Gallon	ASTM D-287	7.4
Specific Gravity @60F, g/ml	ASTM D-1298	0.889

- * Due to continual product research and development, the information contained herein is based on products purchased in the U.S. subject to change without notification. Typical properties may vary slightly.

Additional Information

Part Numbers and UPCs

SAE Grade	30
5 Gal. Pail Part No.	39307
55 Gal. Drum Part No.	39309
260 Gal. Tote Part No.	393047
Bulk	39300

Castrol Trans C 30
01 Aug 2012
Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

BP Lubricants USA Inc., 1500 Valley Road, Wayne, NJ 07470
Telephone: 1,800.462.0835
www.castrol.com/us Email: contactus@bp.com