



Transmax Offroad V 75W-75

Wet brake transaxle fluid

Description

Castrol Transmax Offroad V 75W-75 is a full-synthetic, high-performance, wet brake transaxle fluid suitable for use in applications requiring Volvo Transmission Oil 97304, WB102. This fluid is formulated with a high-performance additive package that allows for longer drain intervals when compared to conventional wet brake transaxle fluids.

Advantages

- High viscosity index, which helps provide effective lubrication over a wide range of temperatures
- Excellent shear stability, which promotes effective gear protection
- Good oxidation stability, which helps against the formation of sludge and other harmful deposits
- Improved low-temperature performance (versus a WB101 fluid)

Typical Characteristics

Name	Method	Units	Offroad V 75W-75
Density @ 15C, Relative	ASTM D4052	g/ml	0.8568
Viscosity, Kinematic 100C	ASTM D445	mm ² /s	7.68
Viscosity, Kinematic 40C	ASTM D445	mm ² /s	40.56
Viscosity Index	ASTM D2270	None	161
Viscosity, Brookfield @ -40C (75W)	ASTM D2983	mPa.s (cP)	33243
Pour Point	ASTM D97	°C	-51
Flash Point, COC	ASTM D92	°C	234

Product Performance Claims

Suitable for use in applications requiring Volvo Transmission Oil 97304, WB102

Transmax Offroad V 75W-75
19 Apr 2022

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

BP Lubricants USA Inc., 1500 Valley Road, Wayne, NJ 07470
Telephone: 1,800.462.0835
www.castrol.com/us Email: contactus@bp.com