



Duratec NG 15W-40

Natural Gas Engine Oil for On-Road Trucks

Description

Castrol Duratec NG 15W-40 is formulated for use in natural gas fueled engines where minimal thermal degradation and good deposit control is expected. Castrol Duratec NG 15W-40 provides outstanding resistance to nitration and oxidation and meets the performance requirements of many of today's mobile natural gas fueled engines. Castrol Duratec NG 15W-40 provides improved cold temperature engine starting and reduced oil consumption relative to single grade natural gas fueled engine oils.

Application

Features and Benefits:

Castrol Duratec NG 15W-40 delivers an advanced detergent/dispersant system that has been designed to reduce deposit formation and improve oxidation characteristics whilst offering excellent corrosion control, TBN retention and outstanding wear control. User Benefits include:

Formulations exhibits excellent thermal and oxidative stability

Provides excellent resistance to acidic corrosion

Specially designed for on road trucks

Exceptional anti-wear and extreme pressure protection

Reduces deposits & maintains engine cleanliness

Wide range of operating temperatures.

Castrol Duratec NG engine oil SAE 15W-40 is designed for use in a wide range of natural gas equipment including – Cummins, Mack, Volvo, and other on road engines requiring a natural gas engine oil.

Specifications

- CES 20085

Typical Characteristics

Name	Method	Units	Duratec NG 15W-40
Appearance	Visual	-	Clear & Bright
Viscosity, Kinematic 100C	ASTM D445	mm ² /s	14.9
Viscosity, Kinematic 40C	ASTM D445	mm ² /s	115
Viscosity Index	ASTM D2270	None	134
Ash, Sulphated	ASTM D874	% wt	.82
Pour Point	ASTM D97	°C	-18

Duratec NG 15W-40

12 Sep 2017

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol (UK) Limited, PO BOX 354, Chertsey Road, Sunbury On Thames, Middlesex, TW16 9AW

www.castrol.com