

Transmax ATF DEXRON®-VI MERCON® LV Multivehicle

Automatic Transmission Fluid

Description

Castrol Transmax ATF DEXRON®-VI MERCON® LV Multivehicle, formulated with Smooth Drive Technology™, is designed for modern automatic transmissions. Its superior technology enables longer transmission life. It is approved and licenced by GM and Ford for use in vehicles requiring their latest ATF specifications and is also suitable for use in most Asian and European automatic transmissions. Transmax ATF DEXRON®-VI MERCON® LV Multivehicle, formulated with Smooth Drive Technology™, delivers enhanced protection and gives drivers a smoother drive for longer.

Advantages

- OEM approved and licensed by Ford (MERCON® LV) and GM (DEXRON®-VI)
- Low viscosity formula for maximum fuel efficiency in modern automatic transmissions
- Enhanced friction durability for smooth transmission performance
- Superior high temperature protection to effectively resist oxidation
- Recommended for use in most automatic transmissions

Typical Characteristics

Name	Method	Units	Transmax ATF DEXRON®-VI MERCON® LV Multivehicle
Density @ 15C, Relative	ASTM D4052	g/ml	0.841
Viscosity, Kinematic 100C	ASTM D445	mm ² /s	5.9
Viscosity, Kinematic 40C	ASTM D445	mm ² /s	30.2
Viscosity Index	ASTM D2270	None	161
Viscosity, Brookfield @ -40C (75W)	ASTM D2983	mPa.s (cP)	10000
Pour Point	ASTM D97	°C	-54
Flash Point, COC	ASTM D92	°C	218

Product Performance Claims

Ford MERCON® LV, GMDEXRON® -VI
Suitable for use where JASO 1A(03)
JASO 1A LV(13) is required including:

Toyota T III

T IV

WS

Mitsubishi SP II

IIM

III

IV

PA

J3

Mazda ATF M-III

M-V

FZ

Honda/Acura DW 1/Z 1

Nissan Matic D

J

S

JWS 3314/3317/ 3309

Suzuki AT Oil 5D06

2384K

Isuzu

Subaru F6

Red 1

Daihatsu AMMIX ATF D-III Multi

D3-SP

Hyundai/Kia SP III

SP IV

Also suitable for use in 6-speed automatics from Audi

BMW

Mini-Cooper

Jaguar

Peugeot/Citroen

Saab

Volvo

VW

Porsche

and all vehicles where Dexron III or Mercon SP is required.

Transmax ATF DEXRON®-VI MERCON® LV Multivehicle

21 Feb 2019

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

BP-Castrol (Thailand) Limited, 3 South Sathon Road, Yannawa, Sathon, Bangkok 10120, Thailand

Technical Advice Line: 662 684 3591 Customer Service: 662 684 3555

www.castrol.com