



Castrol Act>evo 4T 10W-40

Continuous Protection

Description

Did you know that most engine wear happens when your engine is warming up? Ordinary engine oils drain off engine parts when the engine stops leading to wear during warm up.

Castrol Act>evo 4T 10W-40 is uniquely formulated with Actibond™ Molecules that cling to engine parts even when the engine is switched off, providing a protective layer from the moment you start your engine.

Application

Castrol Act>evo 4T 10W-40 is suitable where API SG (or below) and JASO MA2 are recommended.

Advantages

The Castrol Act>evo 4T formulation with Actibond Molecules™:

- Cling to engine parts providing a continuous layer of protection during start-up and beyond
- Clinging action gives up to 70% wear reduction in comparison with other JASO MA2 oils, dramatically increasing engine life*
- Provide superior protection from high temperature carbon deposits, enabling the engine to retain its performance for longer
- Delivers excellent thermal stability for enhanced protection and resistance to oil burn-off at temperature extremes

Suitable for all makes of 4-stroke bikes, both carburetor and fuel injected. Always follow the vehicle manufacturer's recommendations.

*versus JASO MA2 oil without Actibond in cam wear index tested

Typical Characteristics

Name	Method	Units	Act>evo 4T 10W-40
Density @ 15C, Relative	ASTM D4052	g/ml	0.88
Viscosity, Kinematic 100C	ASTM D445	mm ² /s	14.0
Viscosity, Kinematic 40C	ASTM D445	mm ² /s	93
Viscosity Index	ASTM D2270	None	154
Flash Point, PMCC	ASTM D93	°C	>180

Product Performance Claims

API SG
JASO MA-2

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Castrol Act>evo 4T 10W-40
05 Jul 2019
Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

199 Oxford Road, Dunkeld, Johannesburg, 2196, South Africa
+27 11 488 5111, 0860 222 166 (SA), 0800 111 551 (SA)
www.castrol.co.za