

# CASTROL® RADICOOOL™ SF-O PREMIX

---

Castrol Radicool SF-O Premix, a heavy-duty, nitrite-free, extended-life antifreeze/coolant, is a premium quality, Organic Acid Technology (OAT), ethylene glycol-based fluid. Specially formulated with advanced additive technology, this product provides extended service maintenance protection in heavy duty applications without the addition of SCAs, and meets nitrite-free coolant requirements of many industry-leading OEMs.

## ADVANTAGES:

---

Castrol Radicool SF-O Premix is your cooling system's best defense.

- Extended service life of 1,000,000 miles or 20,000 hours.\*
- Free of phosphates, silicate, nitrites, amines and borates.
- Offers excellent wet sleeve liner cavitation protection.
- Contains better heat transfer properties than conventional coolants requiring SCAs.
- Eliminates maintenance with no SCAs required.
- Provides freeze and boil-over protection.
- Extended life corrosion protection for steel, solder, copper, iron, brass and aluminum.
- High-quality defoamer system, non-harmful to hoses, plastics or gaskets.
- Compatible with most major American brands of coolant technologies including conventional and Organic Acid Technology (OAT).



\*HD Extender may be needed based on water quality.

IT'S MORE THAN JUST OIL. IT'S LIQUID ENGINEERING.®



# CASTROL® RADICOOOL™ SF-O PREMIX

## PERFORMANCE SPECIFICATIONS\*

ASTM D3306

ASTM D6210

ASTM DA7583

Behr Radiator

Caterpillar EC-1

Cummins (Diesel/NG) CES 14603

Daimler DBL 7700.00

Daimler MS-7170

Detroit Diesel 93K217

Ford WSS-M97B44-D

GM GMW3420 International

John Deere JDS-G135

Komatsu KES 07 892

Mack GS17004

MAN 324 Type SNF

Mercedes Benz 325.3

MTU 5048

Navistar CEMS B-1 Type IIIA

Paccar CS0185

TMC RP 338A

Volvo / Mack 20774185

\*Meets or exceeds the listed performance specifications.

## TYPICAL PROPERTIES

## RADICOOOL SF-O PREMIX

Appearance

Clear

Color

Red

pH

8.6

Boiling Point

226°F (108°C)

Freeze Point

-34°F (-36°C)

## SHIPPING INFORMATION

## STEEL DRUMS

## TOTES

Package Quantity

55 Gallons

275 Gallons

Package Dimensions

23.5"Dx34.5"H

45.3"x40"x48"

Gross Container Weight

≈530 Pounds

≈2595 Pounds

Gross Weight on Pallet

≈2170 Pounds

≈2595 Pounds

Quantity Per Pallet

4

1

Pallet Dimensions

45"x45"x39.4"

40"x48"x45.3"

Weight Per Gallon

≈9 Pounds

≈9 Pounds

Weight Per Gallon

8.94#

8.94#

All reasonable care has been taken to ensure that the information contained herein is accurate as of the date of printing. Freedom to use any patent owned by Castrol® or others is not to be inferred from any statement contained herein. Test results listed are typical properties only. Formula and blending changes may result in slight color or appearance changes.