

Castrol Radicool SF-O Premix

Ready to use engine coolant and antifreeze

Description

Castrol Radicool SF-O Premix is a silicate free ready-mixed antifreeze, formulated using advanced organic acid technology (OAT), and works over a wide operating temperature range for effective engine cooling in all climates.

Castrol Radicool SF-O Premix requires no customer dilution therefore ensures the correct concentration is always used, providing year round protection against corrosion, and offers freezing protection down to -36°C.

Application

Castrol Radicool SF-O Premix is a long-life coolant based on monoethyleneglycol, it is suitable for use in a wide range of vehicles, including cars, trucks and buses, for both petrol and diesel engines. In contrast to traditional antifreeze coolants, Castrol Radicool SF-O Premix does not contain Amines, Nitrites, Phosphates, Silicates or other inorganic inhibitors.

For maximum performance Castrol Radicool SF-O Premix should not be mixed with other coolants. It is therefore recommended that cooling systems should be drained and flushed before re-filling with diluted Castrol Radicool SF-O Premix.

Advantages

The special inhibitor package used in Castrol Radicool SF-O Premix enables longer drain intervals with optimal protection against corrosion, cooling system blockage, overheating and freezing.

Other benefits are

- Longer operational life by allowing extended drain intervals of 3 years plus
- Longer life means reduced costs and less possibility of harm to the environment
- Outstanding corrosion protection and cooling performance in engines employing cast iron and / or aluminium and also in cooling systems with aluminium and / or copper alloys
- The additive technology in the product prevents build-up of calcium deposits from top up with hard water
- Its formulation is based on monoethylene glycol combined with special OAT inhibitor additive technology
- Protection against cavitation corrosion and rust
- Effective lubrication of water pump
- Suitable for use in mixed fleets

Typical Characteristics

Name	Method	Units	Castrol Radicool SF-O Premix
Appearance	Visual	-	Free and Clear
Sediment mg/L	Supplier	mg/L	Not Present
Colour, Visual	Visual	-	Red
Freezing Point °F	ASTM D1177	°F	- 38
Specific Gravity at 68°F	ASTM D1122	None	1.0795

Product Performance Claims

ASTM D3306 (III)
ASTM D6210
ASTM D7583
BS - BS BS6580

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Castrol Radicool SF-O Premix

30 Jul 2018

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

BP Lubricants USA Inc., 1500 Valley Road, Wayne, NJ 07470

Telephone: 1,800.462.0835

www.castrol.com/us Email: contactus@bp.com