



## Super Snowmobile 2T

Castrol Super Snowmobile 2T

### Description

Castrol Super Snowmobile 2T provides superior protection for 2-stroke snowmobile engines. Castrol Super Snowmobile 2T is a high detergent, low ash forming, 2-stroke lubricant specifically formulated for snowmobile injector systems.

### Application

Meets the engine protection requirements of all makes of snowmobiles including those calling for API Service TC specification.

### Advantages

Advantages

Castrol Super Snowmobile 2T:

- Flows readily at temperatures to minus 40C thus ensuring no excess wear due to oil starvation.
- Can be used with the same confidence on pre-mix systems.

### Typical Characteristics

Name	Method	Units	Typical Results
Appearance	Visual	-	Blue
Viscosity, Kinematic 100C	ASTM D445	mm <sup>2</sup> /s	13.56
Pour Point	ASTM D97	°C	- 42 max
Flash Point, PMCC	ASTM D93	°C	60 min
Viscosity, Kinematic 40C	ASTM D445	mm <sup>2</sup> /s	21.4
Colour	ASTM D1500	-	Blue

### Product Performance Claims

API TC  
Super Snowmobile 2T  
18 Nov 2016

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

BP Lubricants USA Inc., 1500 Valley Road, Wayne, NJ 07470  
Telephone: 1,800.462.0835  
www.castrol.com/us Email: contactus@bp.com